you can

Canon

iR150VPe

Black & White Professional Print Systems

Outstanding performance from Canon



When you need a high speed, high volume machine for the most demanding production environment, turn to the iR150VPe.

Capable of a super-quick 150 prints-perminute and volume production of up to

5 million prints per month, it's a machine that thrives on responsibility. Configurable with up to 12,000 sheets in-line from nine different sources, and catering for throughput of up to 266 gsm in weight, it's the ultimate machine for high volume digital print production environments.

A modular production system, allowing you to select a configuration to maximise productivity in your own environment.

Specifications iR150VPe

MAIN UNIT Imaging System	Electrophotographic Process Up to 5,000,000 impressions/month* TCP/IP,SPX/IPX,EtherTalk,NetBEUI IPDS,PostScript,PCL_PDF,GIF,IPEG,TIFF¹ 364 x 470mm (14.33"x 18.5")** 178 x 210mm (7"x 8.27")** 600 dpi x 600 dpi Up to 9 Paper Drawers*** 2 x 1,000 Sheets +2,000 Sheets per paper supply module 12,000 Sheets** 150 ppm (A4) 75 ppm (A3) 60 to 266 gsm (All Cassettes)² 200 -240 V,50 Hz,16 Amps, 3 Phase 1,630mm x 3,940mm x 1,190mm 1469 Kg
ACCESSORIES PAPER SUPPLY OPTIONS	
PAPER SUPPLY MODULE (SECOND MODULE OPTIONAL) Number of Paper Drawers Paper Capacity Paper Sizes Paper Weights Power Source Dimensions (H x W x D) Weight	3 2 x 1,000 Sheets +2,000 Sheets 178 x 210mm to 356 x 457mm** 60 to 266 gsm² Directly from Main Unit 1,143mm x 790mm x 850mm 247 Kg
POST PROCESS INSERTER (OPTIONAL) Number of Paper Drawers Paper Capacity Paper Sizes Paper Weights Tray Capacity Power Source Dimensions (H x W x D) Weight	3 4,000 Sheets 178 x 210mm to 364 x 470mm** 60 to 266 gsm² 2 x 1,000 Sheets +2,000 Sheets Directly from Main Unit 1,257mm x 787mm x 851mm 277 Kg
FINISHERS BASIC FINISHER (STANDARD) Paper Weights Paper Sizes Number of Trays Tray Capacity Staple Capacity Document Delivery Staple Positions Staple Type Power Source Dimensions (H x W x D) Weight	Up to 266 gsm² Top Exit Tray: 178 x 210mm to 364 x 470mm Staple Exit Tray: 178 x 210mm to 228 x 356mm 2 Top Tray: 500 Sheets Non-Staple (All Sizes) Staple Exit Tray: 3,000 Sheets (85 Sets Stapled) Up to 100 Sheets Face-down Multiposition Stapling None /Top / Bottom / Both Staple Wire Spool (Max. 50,000 stitches) Directly from Main Unit 1,560mm x 580mm x 860mm 295 Kg

STACKER (OPTIONAL) ⁵ Paper Weights Paper Sizes Number of Trays Tray Capacity Document Delivery Power Requirements Dimensions (H x W x D) Weight	Up to 266 gsm² 178 x 210mm to 364 x 470mm** 1 Tote Wheel Cart (Stacker Dolly) 5,000 Sheets Straight or Offset Face-down 220 V,50 Hz 1,257mm x 844mm x 787mm 204 Kg
BOOKLET MAKER (OPTIONAL) ⁵ Paper Sizes Number of Trays Stitching Capacity Stitching Position Staples Folding Folding Capacity Trimming Power Requirements Dimensions (H x W x D) Weight	356 x 457mm (14"x 18") Conveyor Belt Output - Up to 42 Booklets 2 to 22 Sheets (80 gsm) 2 Centre Staple Positions Max. 50,000 Stitches V-Folding 2 to 22 Sheets Edge Trim Folded Booklets 220 V,50 Hz 1,472mm x 254mm x 584mm 440 Kg
PERFECT BINDER (OPTIONAL) ⁵ Binding Technology Book Thickness Book Size Cover Type Cover Weight Paper Weight Power Requirements Dimensions (H x W x D) Weight	Hot Bind Technology 15 - 350 Sheets (80 gsm), up to 40 mm In-Line Binding: 216 x 279mm (8.5"x 11") Off-Line Binding: 60 x 100 mm to 305 x 356 mm Any Paper 80 - 250 gsm 60 - 160 gsm 220 V or 380 V/400 V/415 V,50 Hz 1,200mm x 2,600mm x 1,800mm 760 Kg
BOURG PERFORATING ROTATING & FOLDING UNIT -BPRF (OPTIONAL) Paper Sizes Power Requirements Dimensions (H x W x D) Weight	A4 & 8.5"x 11"-Up to 279 x 432 mm (11"x17") 220 V,50 Hz 1,290mm x 1,620mm x 780mm 255 Kg
MULTI-STACKER INTERFACE KIT (OPTIONAL)	Supports up to three stackers on one device One kit is required for each additional Stacker
OPTIONAL FEATURES	MICR printing Enhanced Feed Mode PCL Interpreter Extended Paper size Range

- * Depends on customer job stream & number of shifts.
- ** With extended paper size option.
- *** With optional Paper Supply Module.
- Other Data stream support available, please ask for details
 Caliper must fall within 3.5mil to 10mil (0.9mm to 0.25mm) an external supply of compressed air is required for heavier media types, together with the Enhanced Feed Mode option.
- 3 Customised Punch tools are available on request.
- 4 Other scanner options are available, please ask for details.
 5 Stacker is required for Booklet-maker and Perfect Binder.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.

™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



Canon Inc.

www.canon.com

Canon Europa N.V. www.canon-europe.com